

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau(43) International Publication Date  
31 December 2003 (31.12.2003)

PCT

(10) International Publication Number  
**WO 2004/001777 A1**(51) International Patent Classification?: **H01F 7/14, 7/16**(21) International Application Number:  
**PCT/GB2002/002825**

(22) International Filing Date: 19 June 2002 (19.06.2002)

(25) Filing Language: English


(26) Publication Language: English

(71) Applicant (for all designated States except US): **ARVIN-MERITOR LIGHT VEHICLE SYSTEMS (UK) LTD.** [GB/GB]; Fordhouse Lane, Stirchley, Birmingham B30 3BW (GB).


(72) Inventors; and

(75) Inventors/Applicants (for US only): **SPURR, Nigel** [GB/GB]; 16 Pathlow Crescent, Shirley, Solihull B90 2PS (GB). **KALSI, Gurbinder, Singh** [GB/GB]; 59 Wolverhampton Road, Oldbury, Warley, West Midlands**B68 0NF (GB). FISHER, Sidney, Edward** [GB/GB]; 24 Underwood Close, Callow Hill, Redditch, Worcestershire B97 5YS (GB).(74) Agents: **JONES, John, Bryn et al.; Withers & Rogers,** Goldings House, 2 Hays Lane, London SE1 2HW (GB).(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,

[Continued on next page]

(54) Title: **ACTUATOR**

ENGAGEMENT POSITION

2ND RELEASE POSITION  
MECHANICAL RELEASE

(57) Abstract: An actuator including an electromagnetic coil arrangement being movable relative to a magnetic field generator, between first and second positions of the actuator, the actuator being arranged such that, with the actuator in the first position, a pulse of current through the electromagnetic coil arrangement produces a region of magnetic field that repels the magnetic field generator from the first position of the actuator and attracts the magnetic field generator towards the second position of the actuator to move the actuator to its second position.